

Applicants : Teichner et al.
Appln. No. : 10/550,404
Page : 2

AMENDMENTS TO THE SPECIFICATION:

Please add the following paragraph after line 24 on page 2:

--Figure 10A illustrates a side view of the gutter cover shown in Fig. 3 assembled on the gutter bracket shown in Fig. 10;--

Please add the following at the end of line 12 on page 7:

-- More specifically, as best shown in Fig. 4, the fold 58 on gutter cover 50 has a generally U-shaped side elevational shape with generally parallel, opposite wall portions 58a and 59b that are vertically spaced apart and are inclined upwardly at a predetermined angle to define the female coupling member 58 into which the male coupling member 112 on bracket 100 is received and retained, as shown in Fig. 10A. The lower wall portion 58b of fold 58 is created by a reverse bend or doubled over portion 58c that has a closed rearward end 58d that protrudes rearwardly and upwardly towards the back section 56 of gutter cover 50 at the predetermined angle of fold 58, and a necked forward end 58e that extends forwardly and downwardly towards the lip section 52 of gutter cover 50 at the predetermined angle of fold 58. The male coupling member 112 on bracket 100 is in the form of a projection that protrudes forwardly and downwardly toward the front member 106 of bracket 100 at the same angle as female coupling member 58. The projection on the male coupling member 112 is closely received and retained in the U-shaped female coupling member 58 to securely mount gutter cover 50 on mounting bracket 100, without the need for separate fasteners.--